TSM1000 I.S. Remote Battery **TankSca** Pack Replacement Instructions



The power of data. Optimized.



WARNING – EXPLOSION HAZARD: DO NOT REPLACE BATTERY PACK WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT.



AVERTISSEMENT – NE PAS REMPLACER LES ACCUMULATEURS SI UNE ATMOSPHERE EXPLOSIVE PUET ÊTRE PRÉSENTE.

The remote battery pack must be disconnected and taken to an unclassified/non-hazardous location before removing the cover.




MARNING – USE ONLY ATEK BATTERY PACK #TSTRB02000



AVERTISSEMENT - UTILISER UNIQUEMENT DES ACCUMULATEURS ATEK #TSTRB02000

Battery Pack Replacement



WARNING - DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT

AVERTISSEMENT - NE PAS OUVRIR EN CAS DE PRESENCE D'ATMOSPHERE EXPLOSIVE

- Remove enclosure cover, disconnect battery cable, and remove used battery pack.
- Remove the foam pieces from the new battery pack and then install new battery pack and reconnect battery cable. Use only ATEK Battery Pack - part # TSTRB02000.
- Re-install cover. Ensure battery cable wiring is not pinched when cover is re-installed.
- Reinstall Remote Battery Pack on tank if removed previously.
 - Do not send used batteries to ATEK. Dispose of them in accordance with local guidelines and regulations.



For questions or problems, **Contact TankScan Technical Support** 877-847-7226

223-0189-002 Rev. C 10/23



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

10025 Valley View Road, Ste. 190 www.atekaccess.com

Email: CCT@tankscan.com



Access the power of technology.