

Partner Solution:


Sensor to Cellular Gateway



The power of data. **Optimized.**

The TankScan TSG Partner Solution is offered for TankScan customers that desire to remotely monitor tank levels utilizing specialty sensors. The solution includes a connectivity gateway from our technology partner that is able to connect to a variety of sensors.

This TankScan partner solution connects to the ATEK Intelligence platform (AIP) which provides tank level information anywhere an Internet connection is available – via computer, tablet or smart phone. Use TankScan analytics to optimize business decisions around preparations and logistics by knowing when a tank is in need of service. Plan fluid deliveries and pick-ups based on the latest information to ensure optimal route efficiency and maximize customer service.




Applications

- Integration of any 4-20mA sensor
- High temperature environments
- Pressurized tanks
- Bulk solids silos
- Tall tanks
- Flow measurements

Other

- 3rd party sensors
- Client provided sensors
- Existing sensors



ATEK Intelligence Platform (AIP) Capabilities

Web-based software can be accessed from any Internet-connected computer.

- Scales from 1 to over 100,000 tanks
- User-friendly dashboard displays accurate measurements across all tanks
- Users can view multiple tanks to simplify site monitoring
- Email alerts provide notification when preset levels are reached
- Multiple users can be authorized to access various levels of data
- Analyze tank data with timely reports

Markets

- Produced Water
- Crude Oil

SPECIFICATIONS	
Sensor Technology	4-20mA or 0-10VDC Sensors, Customer's Choice
Accuracy	Dependent on Sensor Used
Output	Level Data, Temperature, Battery Level
Radio Communication	Cellular 4G LTE Verizon or AT&T
Power Requirements	Non-Rechargeable Lithium Battery Pack
Construction	Weatherproof, Non-corrosive, IP66
Operating Temperature	-31 F to +158 F (-35 C to +70 C)
Battery and Battery Life	7.2 V, 14.5 Ah, Lithium thionyl chloride, non-rechargeable, replaceable; Approximately 2 years (@ 2 reads/transmits per day)
External Power Input	8 VDC to 30 VDC
Approvals	UL60950-1, CAN/CSA C22.2 No. 60950-1-01, IEC 60950-1:2005 (Second Edition); Am1:2009 + Am2:2013, EN 60950-1:2006 / A11:2009 / A1:2010 / A12:2011 / A2:2013 and EN 60950-22:2006; Class 1, Division II, groups A,B,C,D; ANSI/ISA 12.12.01:2015, CAN/CSA C22.2 No 213-15, 1st E; ATEX EN 60079-0:2012+A11:2013, EN 60079-15:2010, ell 3 G Ex nA nC IIC T6 G
Product Warranty	1 Year, Excluding Battery
ORDERING INFORMATION	
Model Numbers	TSGA210C6L1H2, Verizon TSGA310C7L1H2, AT&T

VIEW OUR FULL PRODUCT LINE AT
TANKSCAN.COM

201-0176-000 Rev. A 3/22



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

ATEK Access Technologies
10025 Valley View Road, Ste. 190
Eden Prairie, MN 55344 U.S.A.

PH: 1.800.523.6996
FAX: 1.800.589.3705
+1.218.829.9797

www.atekaccess.com



Access the power of technology.

©2022 ATEK Access Technologies, LLC. All Rights Reserved. TankScan images and marketing materials are protected by various patents, copyrights and/or trademarks. ATEK assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of ATEK are granted by the Company in connection with the sale of TankScan products, expressly or by implication.